





## HOME STANDBY GENERATOR SYSTEMS









#### **FULLY AUTOMATIC 24/7**

No refueling, manual operation, or extension cords needed

## **QUIETEST IN CLASS**

Low-tone muffler design with custom sound baffling system

## MORE FUEL EFFICIENT

Up to 13% better fuel economy than our top competitors









#### EV6A VLLE66

Innovative gullwing enclosure for easy installation and service

### **SUB ZERO/HIGH HEAT**

24V starting system designed to operate from -22° to 104° F

#### **10 YEAR WARRANTY**

Longest standard warranty on the home standby market

## **>**=> (?s

# FASTER INSTALLS, LESS WIRING SAVE MORE TIME, SAVE MORE MONEY

- ▶ aXis is a programmable, upgradable home standby system that gives you access to more options...wirelessly
- Using Power Line Carrier technology aXis eliminates the need for communication wiring\* from generator to switch and modules
- aXis load management allows you to use a smaller generator to manage larger residential homes
- Using aXis load management modules, loads can be assigned priority levels (1-4) allowing for customization on how the home's appliances are managed. Large electric loads can also be locked out entirely while under standby power
- ► aXis Wi-Fi technology allows for onsite setup from phone or tablet \*Wiring for battery charging is required.

## NEW DIGITAL CONTROLS

GENERATOR (HSB)		<b>≢</b> SPECS
Watts (propane / natural gas)	14 kW / 12.5 kW	
Voltage (single phase)	120/240	
Amperage (120/240V)	116.6/58.3 (propane), 104/52 (natural gas)	
Harmonic distortion	Less than 5%	
Main line circuit breaker (A)	65	
Operational volume [db(A)]	62	
Frequency (Hz)	60	
Controls	Digital	NEW!
Weight (lb.)	439	
Dimensions L x W x H (in.)	49 x 28 x 28	

#### NEW SE ATS FAMILY WITH ADVANCED POWER MANAGEMENT

AUTOMATIC TRANSFER SWITCH [ATS]					SPECS
Rating	Service entrance, NEC		Service entrance, CSA		
Amperage (A)	200, 150,	100			NEW!
Enclosure		NEMA 3R			
Material		Aluminum			NEW!
Setup		Wi-Fi (removable external antenna)		NEW!	
Controls		Digital		NEW!	
Power management		Up to 4 priorities (multiple loads per priority)		NEW!	
Dimensions H x W x D (in.)		28 x 20 x 8.3			

## NEW WIRELESS COMMUNICATION

LOAD MANAGEMENT MODUL	E (LMM)			
Amperage rating (A)	50			
Enclosure rating	NEMA 3R			
Material	Aluminum			
Dimensions H x W x D (in.)	8.2 x 5.2 x 3.8			



**CONTROLLER**"